

deleo® Die-Kraft.com

Professional grease remover

Quickly and reliably clears grease deposits.



BENEFITS:

- Reliably removes old and burned-in grease deposits.
- Burned-in grease on electric and gas stoves, barbecue equipment, barbecue skewers and other kitchen surfaces are suitable areas for the pure use of deleo® Viscous Grease Remover.
- Depending on the application, deleo® Viscous Grease Remover can be diluted, so that it has a very high yield. On a painted surface, mix 200 to 400 ml deleo® Viscous Grease Remover with 600 to 800 ml of water.
- The grease remover is suitable for all surfaces, so that no second product is needed.

Make sure you read our application notes.

APPLICATION:

- Ready to use for the above-mentioned surfaces.
- deleo® Viscous Grease Remover can be diluted at a ratio between 1:20 (800 ml water + 200 ml deleo® Viscous Grease Remover) and 1:40 (600 ml water + 400 ml deleo® Viscous Grease Remover).
- Spray on the surface in undiluted form and leave to soak for about 60 seconds.
- Put on rubber gloves and clean the soiled areas in circular motion, using either a kitchen brush or a plastic sponge without a metal surface.
- Next, wash off and then dry. Use deleo® hygienic wipes for this purpose.
- On smooth surfaces, such as extractor hoods and stainless steel roasting pans, apply a wipe, first wet and then damp. This ensures streak-free cleanliness.
- If used in the food industry, rinse surfaces with water.
- In the case of aluminium and zinc, use a dilution factor of 1:30 to 1:40 for cleaning purposes. Apply first in an inconspicuous spot to check for material compatibility.

AREAS OF APPLICATION:

- Extractor hoods, barbecue skewers, barbecue equipment of all kind, gas hobs, ovens, roasting and baking trays, frying pans, saucepans and all metal surfaces in the entire kitchen area.
- deleo® Grease Remover is water-based. It is a highly concentrated intensive cleaning agent for the removal of plant and mineral oils, fats, proteins, separating agents, traces of smoke, wax, fresh paint and pigment ink.
- Biodegradable in accordance with EC guideline.
- Non-flammable, phosphate-free.
- Provides temporary corrosion protection.
Optimum adhesion on vertical surfaces, due to foaming effect and viscosity.

Artikel-Nr.
708.005 bottle

Format
1.000 ml

Packungsgröße
1 carton (6 x 1.000 ml) incl. multiple spray head

www.deleo-die-kraft.com